

11/18/99

11/18/99  
Jc675 U.S. PTO

A

Express Mail Label No. EL172581550

# UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
EN999058

Total Pages in this Submission

## TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application  
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

**METHOD, SYSTEM AND PROGRAM PRODUCTS FOR MANAGING THREAD POOLS OF A COMPUTING ENVIRONMENT TO AVOID DEADLOCK SITUATIONS**

and invented by:

**Gregory David Doolittle, Timothy Peter Krein, Scott Thomas Marcotte**

Jc675 U.S. PTO  
09/443202  
11/18/99

If a CONTINUATION APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Enclosed are:

### Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 47 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☐ Cross References to Related Applications (if applicable)
  - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
  - d. ☐ Reference to Microfiche Appendix (if applicable)
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings (if drawings filed)
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
EN999058

Total Pages in this Submission

**Application Elements (Continued)**

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal                      Number of Sheets 8
- b. ☐ Informal                      Number of Sheets \_\_\_\_\_
4. ☒ Oath or Declaration
- a. ☒ Newly executed *(original or copy)*      ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney      ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application,  
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied  
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

8. ☒ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449      ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class      ☒ Express Mail *(Specify Label No.):* EL172581550

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
**EN999058**

Total Pages in this Submission

**Accompanying Application Parts (Continued)**

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*


16. ☐ Additional Enclosures *(please identify below):*

**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	83	- 20 =	63	x \$18.00	\$1,134.00
Indep. Claims	8	- 3 =	5	x \$78.00	\$390.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$760.00
OTHER FEE (specify purpose)					\$0.00
TOTAL FILING FEE					\$2,284.00

- ☐ A check in the amount of \_\_\_\_\_ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **09-0457(IBM)** as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of **\$2,284.00** as filing fee.
  - ☒ Credit any overpayment.
  - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
  - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).



Signature

**Arthur J. Samodovitz, Esq.**  
Reg. No. 31,297  
IBM Corporation  
Intellectual Property Law  
1701 North Street, N50/040-4  
Endicott, NY 13760  
Telephone (607) 755-3225  
Facsimile (607) 755-3250

Dated: Nov 17, 1999

cc:

## CERTIFICATE OF MAILING BY "EXPRESS MAIL"

In Re Application of: Doolittle et al.

Title: METHOD, SYSTEM AND PROGRAM PRODUCTS FOR MANAGING  
THREAD POOLS OF A COMPUTING ENVIRONMENT TO  
AVOID DEADLOCK SITUATIONS

Attorney Docket No.: EN999058

"EXPRESS MAIL" MAILING LABEL NO. EL172581550


Date of Deposit 11/18/99

I hereby certify that this paper is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and addressed to Assistant Commissioner for Patents, Box PATENT APPLICATION, Washington, D.C. 20231.

Enclosed: New Utility Patent Application Transmittal  
Letter (Large Entity) (3 pp.) (in duplicate)  
U.S. Patent Application -  
Specification (25 pp.); Claims (21 pp.);  
Abstract (1 p.)  
Formal Drawings (8 sheets)  
Declaration and Power of Attorney (3 pp.)  
(     unsigned) (X signed)  
Information Disclosure Statement (2 pp.)  
Information Disclosure Citation w/references  
(1 p.) (9 cited)  
2 Postcards

Denise M. Jurik

(Typed or printed name of person mailing paper or fee)



(Signature of person mailing paper or fee)

APPLICATION  
FOR  
UNITED STATES LETTERS PATENT

APPLICANT(S) NAME: G. D. Doolittle et al

TITLE: Method, System And Program Products For  
Managing Thread Pools Of A Computing Environment  
To Avoid Deadlock Situations

DOCKET NO. EN999058

INTERNATIONAL BUSINESS MACHINES CORPORATION

**Certificate of Mailing Under 37 CFR 1.10**

I hereby certify that, on the date shown below, this correspondence is being deposited with the United States Postal Service in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C., 20231 as "Express Mail Post Office to Addressee".

"Express Mail" Label Number EL172581550

On November 18, 1999

Denise M. Jurik

*Typed or Printed Name of Person Mailing Correspondence*

*Denise M. Jurik*  
Signature of Person Mailing Correspondence

11/18/99  
Date

METHOD, SYSTEM AND PROGRAM PRODUCTS FOR MANAGING  
THREAD POOLS OF A COMPUTING ENVIRONMENT  
TO AVOID DEADLOCK SITUATIONS

Technical Field

5           This invention relates, in general, to processing requests within a computing environment, and in particular, to ensuring that a pool of threads is available to process the requests, such that a deadlock situation is avoided.

Background Art

10           In various computing environments, a request by one requester (e.g., a client) for a resource cannot be satisfied until control of that resource is relinquished by a previous requester. One such computing environment is the Distributed File System (DFS) offered by International  
15 Business Machines Corporation (IBM).

          The DFS product, which supports Server Message Block (SMB) clients, is used by, for example, the OS/390 operating system of IBM to provide a file serving protocol. DFS and specifically, SMB (also known as Common Internet File System  
20 (CIFS)), allows clients to cache data via a form of locking, called an opportunistic lock (oplock). An oplock is requested on the file open SMB request and the server grants an oplock depending on whether other clients have the file open at the same time or not. If a client has an oplock,  
25 then that client can cache file data and/or byte range lock

requests for that file, and can perform read-ahead and write-behind optimizations.

Oplocks are broken by the server when another client attempts to open the file or when another client requests an operation that might change the file, such as a rename or delete. In these cases, the server sends a callback to the client (called an oplock break) that tells the client it lost its oplock. The client responds either with a file close SMB or an oplock break notification via a lockingX SMB. However, if the client has dirty data or cached byte range locks, it is allowed to flush the data and obtain byte range locks before it closes the file or sends the break notification via the lockingX SMB. The client request (or requests) that forced the server to break the other client's oplock is made to wait for the oplock notification or file close from the original client that held the oplock.

Since any client request could possibly wait for a callback and response from one or more clients, there must be processing threads available to handle the callback response(s) from the client(s) holding the oplock or a deadlock could occur. A single thread pool, no matter what the size, cannot solve the problem. For example, assume that Client A currently has a hold (e.g., an oplock or a token) on Resource X (e.g., a file) and is currently updating Resource X. Then, Client B requests that resource. The server breaks the oplock for Resource X, even though Client A is not done updating Resource X. Eventually, Client A sends a response to the callback; however, there

may be no threads in the thread pool to handle the response, since all of the threads are already processing client requests that are waiting for the callback response from Client A.

5           At least two approaches have been taken in an attempt to avoid the above deadlock situation. One approach is referred to as the single pool approach. With the single pool approach, when a thread is to wait for an oplock response, rather than blocking the thread, the thread is  
10   made available to process other requests. Hence, the state of the in-progress operation is saved and the thread is made available to process another request, including an oplock break response. Thus, with this approach, the state must be  
15   maintained for each operation. Further, to make a thread available again for processing requires that each routine called up to the point where it has detected an oplock break is needed, would have to be prepared for a special return code from its callers to see if the operation was completed or was simply placed on hold due to an oplock break  
20   response, and each routine would have to return to its caller to collapse the program stack on the thread to make it available.

          This approach increases the complexity of the code that processes the individual SMBs and also adds increased path  
25   length, since many routines in the path would have to update a state block and also check upon the return of a called routine to determine whether the request was processed or whether it was queued waiting on an oplock break response.



Hence, this approach is considered expensive and a degradation of system performance.

Another approach is a dual pool approach. With this approach, a primary thread pool handles any client requests, while a secondary thread pool only handles requests that could not possibly block waiting to obtain a hold on a resource. Hence, the secondary pool handles requests that were guaranteed not to wait on resources, such as requests to store back data or release resources. For this approach, the client indicated on the request whether it was eligible for the secondary pool or not. Thus, it was the responsibility of the client software to provide an indication of what thread pool was to be used by the server and to provide this indication in the request itself.

The dual thread pool scheme avoids deadlock without the expense of implementation or performance degradation of the single pool scheme. However, the problem with the dual pool approach is that client software is required to indicate which thread pools are eligible for the server to use on an individual request basis. Thus, special client software is needed, which results in extra administrative expense to customers.

Based on the foregoing, a need still exists for an approach to avoid deadlocks, which is more efficient, simpler and less expensive than previous approaches, and does not require additional or special client software. A

1 1  
further need exists for an approach that enables the dynamic assignment of thread pools.

### Summary of the Invention

5 The shortcomings of the prior art are overcome and additional advantages are provided through the provision of a method of managing thread pools of a computing environment. In one embodiment, the method includes receiving from a first requester of the computing environment a request to be processed, wherein the request  
10 is waiting on a response from a second requester of the computing environment, and wherein the response is to be serviced by a thread pool selected from a set of one or more eligible thread pools; and dynamically altering the set of one or more eligible thread pools to provide an altered  
15 thread pool set of one or more eligible thread pools, wherein a thread pool of the altered thread pool set is to service the request.

In one example, the dynamic altering is initiated, when it is determined that the request is waiting for the  
20 response.

In another example, the first requester and the second requester are the same requester. Further, in yet another example, the first requester and the second requester are different requesters.

In a further aspect of the present invention, the response is dispatched on a thread of the thread pool. Further, the method includes determining whether the thread pool is appropriate for the dispatched response, and when  
5 the thread pool is inappropriate, redispersing the response onto another thread pool.

In yet a further embodiment, the method includes dynamically re-altering the altered thread pool set to service one or more other responses or one or more other  
10 requests.

In yet a further aspect of the present invention, a method of managing thread pools of a computing environment is provided. The method includes, for instance, dynamically determining which thread pool of a plurality of thread pools  
15 is to be used to process a request; and processing the request using a thread of the thread pool.

Systems and computer program products corresponding to the above-summarized methods are also described and claimed herein.

20 Advantageously, the present invention provides a thread pool management capability that ensures the avoidance of deadlock situations when a client is waiting on a response from one or more other clients or the same client. This capability does not incur the development expense or suffer  
25 from the performance degradation of a single pool solution,

and does not require the special client software of previous dual pool approaches.

Additional features and advantages are realized through the techniques of the present invention. Other embodiments  
5 and aspects of the invention are described in detail herein and are considered a part of the claimed invention.

### **Brief Description of the Drawings**

The subject matter which is regarded as the invention is particularly pointed out and distinctly claimed in the  
10 claims at the conclusion of the specification. The foregoing and other objects, features, and advantages of the invention are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

15 FIG. 1 depicts one example of a computing environment incorporating and using the capabilities of the present invention;

FIG. 2 depicts a more detailed embodiment of various components of one of the computing units of  
20 FIG. 1, in accordance with the principles of the present invention;

FIG. 3a depicts one example of a primary pool used in accordance with the principles of the present invention;

FIG. 3b depicts one embodiment of a secondary pool used in accordance with the principles of the present invention;

5           FIG. 4a depicts one embodiment of the logic associated with creating a client session, in accordance with the principles of the present invention;

10           FIG. 4b depicts one embodiment of the logic associated with receiving a request, in accordance with the principles of the present invention;

FIGs. 4c-4d depict one embodiment of the logic associated with processing requests, in accordance with the principles of the present invention;

15           FIG. 5 depicts one embodiment of a session data structure associated with a client, in accordance with the principles of the present invention;

FIG. 6 depicts one embodiment of a request queue used in accordance with the principles of the present invention;

20           FIG. 7 depicts one embodiment of the logic associated with scheduling a Service Request Block, in accordance with the principles of the present invention; and

FIG. 8 depicts one embodiment of the logic associated with dynamically changing the set of eligible pools to be used in processing requests, in accordance with the principles of the present invention.

### Best Mode for Carrying out the Invention

In accordance with one aspect of the present invention, the set of thread pools eligible for servicing an outstanding request is dynamically determined and/or altered. This set of pools can be determined and/or altered without cancelling the outstanding request and without requiring an extra dispatch of the request. As one example, this capability is used to avoid deadlock situations, when, for instance, one client request cannot be processed until it receives a response (e.g., a callback response) from one or more other clients (or the same client). As used herein, the term client includes, at the very least, a local client, a remote client and/or a local user, as examples.

One embodiment of a computing environment incorporating and using the capabilities of the present invention is described with reference to FIG. 1. A computing environment 100 includes, for instance, at least one computing unit 102 coupled to one or more other computing units 104. In one example, computing unit 102 is a server, while computing units 104 are clients. Each unit includes, for example, one or more central processing units, memory and one or more input/output devices, as is well known in the art.

Computing unit 102 is based, for instance, on the Enterprise Systems Architecture (ESA)/390 offered by International Business Machines Corporation, Armonk, New York. ESA/390 is described in an IBM Publication entitled

5 "Enterprise Systems Architecture/390 Principles of Operation," IBM Publication No. SA22-7201-04, June 1997, which is hereby incorporated herein by reference in its entirety. One example of a computing unit based on ESA/390 is the 9672 Parallel Enterprise Server offered by

10 International Business Machines Corporation.

One or more of computing units 104 are personal computers. As one example, a computing unit 104 is a personal computer executing Microsoft Windows, which runs on the Intel PC architecture.

15 Computing unit 102 is coupled to one or more of computing units 104 via a standard connection, such as any type of wire connection, token ring or network connection, to name just a few examples. One communications protocol used by one or more of these connections is TCP/IP.

20 The above-described computing environment and/or computing units are only offered as examples. The present invention can be incorporated and used within many types of computing units, computers, processors, nodes, systems, workstations and/or environments without departing from the

25 spirit of the present invention. For example, one or more of the units may be based on the Unix architecture or may include the Intel PC architecture. Additionally, while some

of the embodiments described herein are discussed in relation to servers and clients, and in particular, to a file server and clients, such embodiments are only examples. Other types of receivers and requesters of information, other types of servers and other types of computing environments can benefit from the present invention and are thus, considered a part of the present invention.

Additionally, the clients need not be remote from the server. The invention is equally applicable to clients and servers running on the same physical machine, different physical machines or any combination thereof.

Further details of computing unit 102 are described with reference to FIG. 2. As one example, computing unit 102 includes an operating system 202, such as the OS/390 or MVS Operating System offered by International Business Machines Corporation. Running on the operating system is, for instance, a file server 204. File server 204 includes a plurality of layers, such as, for example, an SMBparser layer 206, a Netbios layer 208 and an Asynchronous socket I/O layer 210.

SMBparser layer 206 is the main SMB processing layer that knows the state of the environment relative to the client (e.g., what files are opened, what callbacks are in progress, etc.). When this layer is called, the client session is in a stopped state. Thus, no more requests are received from the client, while it is in this state. The



lowest SMB layers call Netbios to re-enable the session,  
after performing some preliminary processing.

Netbios layer 208 is responsible for maintaining  
communications between the server and the clients. It is a  
5 conduit between the SMBparser layer and the Asynchronous  
sockets layer. Netbios schedules the asynchronous receive  
requests, described below, on behalf of the SMBparser. For  
example, SMBs are packaged in Netbios packets and Netbios  
makes the asynchronous socket calls on behalf of the  
10 SMBparser layer, which performs the work.

Async sockets I/O layer 210 provides the low level  
socket communications that maintain the thread pools used in  
processing client requests. In one example, the Async  
sockets layer uses the POSIX (Portable Operating System  
15 Interface for Computer Environments) Asynchronous IO  
interface to handle communications.

Each of the layers is aware that there are a plurality  
of thread pools to be managed. As one example, the  
plurality of thread pools includes a primary thread pool 300  
20 (FIG. 3a) and a secondary thread pool 302 (FIG. 3b). Each  
thread pool includes zero or more available threads 304 to  
be used by the server in processing an incoming client  
request. In one example, the available threads are stored  
in a last in/first out (LIFO) order. (In another  
25 embodiment, there may be a plurality of primary pools and/or  
a plurality of secondary pools.)

When a client sends a request to a server to be processed, the server obtains an available thread from a selected thread pool in order to process the request. The selected pool is chosen from a set of eligible thread pools, and, in accordance with one aspect of the present invention, the set is dynamically managed, in order to avoid deadlock situations, as described below.

One embodiment of the logic used to process requests of a client is described with reference to FIGs. 4a-4d. In particular, FIG. 4a describes one embodiment of the logic used to create a client session; FIG. 4b describes one embodiment of the logic used to schedule the request; and FIGs. 4c-4d describe one embodiment of the logic used to process the request.

Before a client communicates with a server, a client session is created, as described with reference to FIG. 4a. Initially, the operating system notifies the file server of a new client session that has been dispatched on a thread pool, such as the primary thread pool, STEP 400 (FIG. 4a).

Thereafter, the new client session is created, STEP 402. In particular, each client session is represented by a session data structure, which is used to store information relating to the particular client session. In one example, a session structure 500 (FIG. 5) includes an opportunistic lock (oplock) count indicating the number of outstanding oplocks for the client. This information is employed, for instance, to determine the set of eligible pools to be used

to process a request. For example, if the count is zero, then the set of pools includes only the primary pool. However, a count greater than zero indicates that at least one other pool (e.g., a secondary pool) is also to be used  
5 to process the client requests. The session structure also includes a lock used for serialization, as described below.

Returning to FIG. 4a, after a client session is established, an asynchronous receive (async\_recv) function is issued to allow notification of when a client request  
10 arrives at the server, STEP 404. In one example, it is Netbios that asynchronously schedules the request for the receipt of the data. The asynchronous receive call includes a pool mask indicating the allowable pools to be used to dispatch the work thereon. In one example, this pool mask  
15 is set dynamically (i.e., without human intervention and/or without the use of client code) using a setpoolmask function, which is described in further detail below. Since this pool mask is being set at the start of a client session, the pool mask is initially set to one pool (e.g.,  
20 the primary pool). Thus, the asynchronous receive function allows the efficient specification of allowable thread pools to be used when the next data request comes in from the associated client.

The asynchronous request is represented, in one  
25 embodiment, by a request data structure that includes information relating to the request. In one example, a request data structure 600 (FIG. 6) includes a mask of the thread pools that are eligible to service the request. For

example, the mask includes a bit for each possible pool. Then, if the pool is eligible for processing, the bit is set on. If, however, the pool is not eligible for processing, then it is turned off.

5           One or more of the requests may be located on a request queue 602, which includes any client requests that could not be attached to a service thread, when it arrived at the server. (The request structure, as well as the other data structures described herein are protected by a main lock.)

10           Referring now to FIG. 4b, when a client request (also referred to as an SMB request or data) is received by the server, STEP 406, a Service Request Block (SRB) is scheduled by the operating system, which runs SRB code to dispatch the request to an available thread from an eligible pool  
15 (determined by the pool mask in the request), STEP 408. This SRB code does not do much processing at this time, since only the header portion has arrived. For instance, it does not examine the SMB to see what it is. It does, however, know the set of eligible pools. Thus, it checks  
20 the eligible pools (in order, as one example) and dispatches the request onto an available service thread of an eligible pool or puts the request on a global queue (e.g., the request queue), if all threads are busy.

          Further details associated with one embodiment of the  
25 SRB logic are described with reference to FIG. 7. The SRB logic receives as input an address of the request block,

which contains the relevant information about the request, including the pool mask.

Initially, a main lock is obtained for the request queue, STEP 700. This lock allows information in the pool mask to be retrieved without being concerned that the information can simultaneously be changed, STEP 700. Then, an eligible pool of the pool mask is selected and checked for an available service thread, STEP 702. In one example, the pool to be checked is selected based on pool order. For instance, the primary pool is first checked and then the secondary pool (or other pools), if necessary. This makes it less likely that requests are processed on the secondary pool, and hence, less likely that a redispatch (described below) will be necessary.

If an available service thread is located, INQUIRY 704, then the service thread is removed from the pool, STEP 706, and the state of the request is set to Dispatched, STEP 708. This state indicates that the request was given to a service thread. Other states associated with a request include New indicating that the request has been sent to the system at some undetermined time (an SRB will be scheduled when data is available); Queued indicating that the request is on the request queue; Complete specifying that the request completed successfully; Failed indicating that the request failed; and Cancelled indicating that the request was cancelled.

If there was no available service thread, INQUIRY 704, then the request is added to the request queue, STEP 710, and the state of the request is set to Queued, STEP 712.

After dispatching or queuing the request, the main lock  
5 for the request queue is released, STEP 714. Subsequently, a determination is made as to whether a service thread was taken from the pool in STEP 706, STEP 716. If so, then POST processing is performed to dispatch the request on the processor on the available service thread, STEP 718.  
10 Thereafter, or if a service thread was not taken, then processing of the SRB is complete.

Subsequent to scheduling the Service Request Block, the request is processed, assuming that the request state was set to Dispatched by the SRB code. One example of this  
15 processing is described with reference to FIGs. 4c-4d.

At this point, the request is running on a service thread and the service thread knows its pool number. Thus, SMBparser is called via, for example, Netbios, which passes the pool number to SMBparser, STEP 410 (FIG. 4c). SMBparser  
20 performs some preliminary SMB processing, STEP 412, and another asynchronous receive function is issued to allow notification of the next request, STEP 414.

Additionally, processing continues for the request running on the service thread. Initially, the session  
25 associated with the client issuing the request is locked, STEP 416, and a determination is made as to whether the

request is a callback response, INQUIRY 418. Should the request be a callback response, then the opcount is decremented, STEP 420, and a further determination is made as to whether the opcount is equal to zero, INQUIRY 422. If  
5 the opcount is zero indicating no further callback responses are needed, then setpoolmask is called to set the eligible thread pools to the primary pool, as one example, STEP 424. Thereafter, the session is unlocked, STEP 426.

Returning to INQUIRY 418, if this request is not a  
10 callback response or if the opcount is not equal to zero (INQUIRY 422), then setpoolmask is not called, at this time, and the session is unlocked, STEP 426.

Subsequent to unlocking the session, a determination is made as to whether the pool associated with the thread  
15 servicing the request is legal, INQUIRY 428 (FIG. 4d). In particular, in one example, whenever a new SMB comes in, the pool number of the processing thread is passed from Async sockets to SMBparser, and the lower layers of SMBparser, as one example, examine the pool of the running thread to  
20 determine if it is legal. In one instance, the SMBparser checks to see whether the SMB is a request for a file that has an oplock held (i.e., is it a callback response). If the SMB is for an operation against an oplocked file, then it is eligible to be run on the secondary pool (it will not  
25 block because it already has an oplock) in addition to the primary pool. Any other SMB requests or requests for non-oplocked files are run only on the primary pool, in one example.

Thus, if the pool is legal, INQUIRY 428, then the SMB is processed on the thread, STEP 430. Thereafter, a determination is made by, for instance, the SMBparser layer, as to whether a callback to one or more other clients (or the same client) is needed in order to obtain information desired or needed by the processing request. In other words, will the request need to wait for one or more callback responses, INQUIRY 432.

If a callback is not needed, then the request is simply processed to completion (i.e., successful completion, failed, cancelled) on the thread selected earlier, and a reply is sent to the requesting client, STEP 434. Subsequently, the request queue is checked to see if other requests are eligible to be processed, STEP 436.

However, if a callback to one or more other clients (or the same client) is needed, then a session associated with one of the clients to receive the callback is locked, STEP 438, and the opcount is increased indicating an outstanding response, STEP 440. Additionally, a determination is made as to whether the current poolmask (indicated in the request block) is correct, INQUIRY 442. That is, a determination is made as to whether the poolmask reflects that both the primary and secondary thread pools are eligible for use.

If the poolmask already indicates that both the primary and secondary thread pools are eligible to be used, then the setpoolmask function does not need to be called. However, if the poolmask is not correct, then the setpoolmask



function is performed in order to dynamically change the set of eligible thread pools for the client to receive the callback and to send the callback response, STEP 444. In particular, the setpoolmask function is issued to allow the  
5 next requests (e.g., the callback responses) to be processed by one of a plurality of pools.

The setpoolmask function can dynamically change the eligible pools of an outstanding request without cancelling the request or without extra dispatching of the request.  
10 However, as described below, there is a race condition inherent in the processing. That is, by the time setpoolmask is presented to Async sockets (the Async sockets code includes the setpoolmask code, in one instance), it may be too late to alter the set of eligible pools or the data  
15 could be coming in right at the time setpoolmask is called. Thus, further action is taken, as described below.

One embodiment of the logic associated with the setpoolmask capability is described with reference to FIG. 8. As described above, the setpoolmask code is called by  
20 SMBparser or Netbios when, for instance, it is determined that the request is waiting for a response, and more particularly, in one example, before a callback is to be issued to a client. Input to the setpoolmask code is an address of the request block with the relevant information  
25 and the new pool mask to be used (e.g., primary pool and secondary pool), as determined by the server.

Initially, a verification is performed of the request handle obtained from the request block corresponding to the request to ensure its validity, STEP 800. If it is invalid, INQUIRY 802, then processing of the setpoolmask function is complete, STEP 803. However, if it is valid, then the main lock of the request queue is obtained, STEP 804.

Subsequently, the pool mask in the appropriate request block is set to the input pool mask, STEP 806. Next, a determination is made as to whether the asynchronous request state is queued and whether the set of eligible pools is expanding, INQUIRY 808. That is, a determination is made as to whether the eligible pool list has changed. If the request is queued and the set of eligible pools has changed, then the request is removed from the queue, STEP 810, and the dispatch code is run to determine if the request could be processed by any of the new additional pools (to avoid deadlock), STEP 812. If it can, then a new pool is selected; if not, it is put back on the queue.

Returning to INQUIRY 808, if the asynchronous request is queued, but the set of pools is not expanding, then no action is taken and the race to change the set of eligible pools before the callback response is dispatched on the same pool waiting for the response (thereby causing a deadlock) may have been lost. That is, setpoolmask tries to honor the request, but it may be too late in some cases (response may already be dispatched).

After running the dispatch code or if the set of pools is not expanding, the main lock for the request queue is released, STEP 814, and the processing of setpoolmask is complete, STEP 803.

5        Since setpoolmask cannot guarantee that the setpoolmask request to change the set of eligible pools can be honored, for each SMB that is dispatched, the Asynchronous sockets layer passes the number of the pool corresponding to the running thread (i.e., thread of the SMB) to the upper layers  
10    (e.g., Netbios and SMBparser layers). Using this information (e.g., pool number), these layers make a determination as to whether the request should be redispatched to avoid a deadlock. In particular, these layers determine whether the pool is legal, as described  
15    above.

Returning to FIG. 4d, subsequent to setting the poolmask, a callback is issued to the client having the desired information, STEP 446. Thereafter, the target session of that client is unlocked, STEP 448, and a  
20    determination is made as to whether there are any other clients to callback, INQUIRY 450. This determination is made by, for instance, checking the oplocks for other clients.

When there are more clients to callback, processing  
25    continues with STEP 438, as described above. However, when there are no more outstanding callbacks, the service thread is put into a wait state (i.e., it goes idle and is

ineligible for dispatch) until all of the responses come back, STEP 452. Thereafter, the SMB is processed, and the reply is sent to the requesting client, STEP 434.

5 Additionally, the request queue is checked to determine if there is another eligible request on the request queue to be processed, STEP 436.

Returning to INQUIRY 428, if it is determined that the pool is illegal, then the request cannot be processed on the thread currently servicing the request. Thus, the lowest  
10 SMB parser layers, as one example, return a special return code to Netbios. Netbios then calls Async sockets to redispatch the request onto an eligible pool, which is the primary pool in this example, STEP 456. Netbios returns to Async sockets, which makes the running thread available to  
15 the pool. Hence, it could be that due to race conditions, requests unrelated to the callback come in that require redispatch from the secondary pool to the primary pool.

It should be noted that although a redispatch can be expensive in terms of CPU, it typically does not happen.  
20 The race is usually won by setpoolmask, which simply sets the mask and future requests come in on the appropriate pool(s). Clients usually respond to an oplock immediately, so unless a client request has come in coincidentally when an oplock break is sent out and there are no available main  
25 pool threads, no redispatch is necessary. Also, in general, the main thread pool is set large relative to the secondary pool (the secondary pool is there, in one example, just to avoid deadlock). Thus, most requests, even oplock break

responses, are simply processed on the primary pool, which does not require redispatch. Thus, in a large majority of the oplock break cases, changing the pool selection results in the setting of a bit mask (e.g., a machine word) and no  
5 redispatching is necessary resulting in a very efficient scheme. Only the lowest layer of the SMBparser component needs to deal with redispatch. The higher layers in the SMBparser, along with the layers above that (e.g., the file system interface and the opportunistic lock handling code)  
10 do not need to worry about what pool the request is running on, redispatch, or anything else related to this scheme.

Described in detail above is one embodiment of a pool management capability that allows the dynamic setting of eligible pools to be used to process requests. The set of  
15 pools is dynamically changed in order to avoid deadlock situations, especially when a client request is waiting for a callback response from one or more other clients.

In one aspect of the present invention, a dual pool solution is provided that handles thread pool assignment  
20 dynamically with no indication from the client request which pool it can use. The dynamic pool assignment mechanism is efficient and can be used in a variety of computing environments, including, but not limited to, any client/server environments, where client requests might need  
25 to block on responses from other clients.

The present invention can be included in an article of manufacture (e.g., one or more computer program products)

having, for instance, computer usable media. The media has embodied therein, for instance, computer readable program code means for providing and facilitating the capabilities of the present invention. The article of manufacture can be  
5 included as a part of a computer system or sold separately.

Additionally, at least one program storage device readable by a machine, tangibly embodying at least one program of instructions executable by the machine to perform the capabilities of the present invention can be provided.

10 The flow diagrams depicted herein are just exemplary. There may be many variations to these diagrams or the steps (or operations) described therein without departing from the spirit of the invention. For instance, the steps may be performed in a differing order, or steps may be added,  
15 deleted or modified. All of these variations are considered a part of the claimed invention.

Although preferred embodiments have been depicted and described in detail herein, it will be apparent to those skilled in the relevant art that various modifications,  
20 additions, substitutions and the like can be made without departing from the spirit of the invention and these are therefore considered to be within the scope of the invention as defined in the following claims.

## Claims

What is claimed is:

1           1.    A method of managing thread pools of a computing  
2    environment, said method comprising:

3                    receiving from a first requester of said computing  
4    environment a request to be processed, said request  
5    waiting on a response from a second requester of said  
6    computing environment, and wherein said response is to  
7    be serviced by a thread pool selected from a set of one  
8    or more eligible thread pools; and

9                    dynamically altering said set of one or more  
10   eligible thread pools to provide an altered thread pool  
11   set of one or more eligible thread pools, wherein a  
12   thread pool of the altered thread pool set is to  
13   service said response.

1           2.    The method of claim 1, wherein said dynamically  
2    altering comprises setting a pool mask associated with said  
3    response to indicate said one or more eligible thread pools.

1           3.    The method of claim 2, wherein said pool mask is  
2    included within a data structure associated with said  
3    response.

1           4. The method of claim 1, wherein said dynamically  
2 altering is initiated when it is determined that said  
3 request is waiting for said response.

1           5. The method of claim 1, further comprising selecting  
2 said thread pool from said altered thread pool set to  
3 service said response.

1           6. The method of claim 5, wherein said selecting  
2 comprises:

3                   determining which, if any, thread pools of said  
4 altered thread pool set were not included in said set  
5 of one or more eligible thread pools, thereby providing  
6 one or more new thread pools; and

7                   selecting said thread pool from said one or more  
8 new thread pools.

1           7. The method of claim 1, further comprising  
2 dispatching said response on a thread of said thread pool.



1           8. The method of claim 7, further comprising:  
  
2                 determining whether said thread pool is  
3                 appropriate for the dispatched response; and  
  
4                 redispatching said response onto another thread  
5                 pool when the thread pool is inappropriate.

1           9. The method of claim 1, further comprising  
2     dynamically re-altering said altered thread pool set to  
3     service one or more other responses or one or more other  
4     requests.

1           10. The method of claim 9, wherein said dynamically  
2     re-altering is performed when there are no outstanding  
3     callbacks to be responded to by said second requester.

1           11. The method of claim 10, further comprising  
2     determining whether there are any outstanding callbacks,  
3     said determining referencing a data structure associated  
4     with said second requester.

1           12. The method of claim 1, further comprising  
2     selecting a thread pool to service said request from a  
3     request set of one or more eligible thread pools, wherein  
4     said selecting is based on an ordering of said one or more  
5     eligible thread pools.

1        13. The method of claim 12, wherein said ordering  
2 comprises having a primary thread pool selectable before any  
3 secondary thread pool.

1        14. The method of claim 1, wherein said receiving  
2 comprises receiving said request by a server of said  
3 computing environment, and wherein said first requester is a  
4 first client and said second requester is a second client.

1        15. The method of claim 14, wherein said server is a  
2 file server.

1        16. The method of claim 14, wherein at least one of  
2 said first client and said second client runs on a same  
3 physical computer of said computing environment as said  
4 server.

1        17. The method of claim 14, wherein at least one of  
2 said first client and said second client runs on a different  
3 physical computer of said computing environment than said  
4 server.

1        18. The method of claim 1, wherein said dynamically  
2 altering is performed by a server of said computing  
3 environment.

1        19. The method of claim 1, wherein said thread pool of  
2 said altered thread pool set is to service said response to  
3 avoid a deadlock with said request awaiting said response.

1           20. The method of claim 1, wherein said dynamically  
2 altering comprises receiving no indication from said second  
3 requester of which thread pools are to be included in said  
4 altered thread pool set.

1           21. The method of claim 1, wherein said first  
2 requester and said second requester are the same requester.

1           22. The method of claim 1, wherein said first  
2 requester and said second requester are different  
3 requesters.

1           23. A method of managing thread pools of a computing  
2 environment, said method comprising:

3                   dynamically determining which thread pool of a  
4 plurality of thread pools is to be used to process a  
5 request; and

6                   processing said request using a thread of said  
7 thread pool.

1           24. The method of claim 23, wherein said dynamically  
2 determining is performed when said request is a callback  
3 response to another request.

1           25. The method of claim 23, wherein said computing  
2 environment comprises at least one server and at least one  
3 client, and wherein said request is issued by a client of  
4 said at least one client and received by a server of said at  
5 least one server, and wherein said dynamically determining  
6 is performed by said server.

1           26. The method of claim 25, wherein said dynamically  
2 determining comprises receiving no indication from said  
3 client of which thread pool is to be used.

1           27. A system of managing thread pools of a computing  
2 environment, said system comprising:

3           means for receiving from a first requester of said  
4 computing environment a request to be processed, said  
5 request waiting on a response from a second requester  
6 of said computing environment, and wherein said  
7 response is to be serviced by a thread pool selected  
8 from a set of one or more eligible thread pools; and

9           means for dynamically altering said set of one or  
10 more eligible thread pools to provide an altered thread  
11 pool set of one or more eligible thread pools, wherein  
12 a thread pool of the altered thread pool set is to  
13 service said response.

1           28. The system of claim 27, wherein said means for  
2 dynamically altering comprises means for setting a pool mask  
3 associated with said response to indicate said one or more  
4 eligible thread pools.

1           29. The system of claim 28, wherein said pool mask is  
2 included within a data structure associated with said  
3 response.

1           30. The system of claim 27, wherein the dynamically  
2 altering is initiated when it is determined that said  
3 request is waiting for said response.

1           31. The system of claim 27, further comprising means  
2 for selecting said thread pool from said altered thread pool  
3 set to service said response.

1           32. The system of claim 31, wherein said means for  
2 selecting comprises:

3                   means for determining which, if any, thread pools  
4 of said altered thread pool set were not included in  
5 said set of one or more eligible thread pools, thereby  
6 providing one or more new thread pools; and

7                   means for selecting said thread pool from said one  
8 or more new thread pools.

1           33. The system of claim 27, further comprising means  
2 for dispatching said response on a thread of said thread  
3 pool.

1           34. The system of claim 33, further comprising:

2                   means for determining whether said thread pool is  
3           appropriate for the dispatched response; and

4                   means for redispaching said response onto another  
5           thread pool when the thread pool is inappropriate.

1           35. The system of claim 27, further comprising means  
2           for dynamically re-altering said altered thread pool set to  
3           service one or more other responses or one or more other  
4           requests.

1           36. The system of claim 35, wherein said means for  
2           dynamically re-altering is performed when there are no  
3           outstanding callbacks to be responded to by said second  
4           requester.

1           37. The system of claim 36, further comprising means  
2           for determining whether there are any outstanding callbacks,  
3           said determining referencing a data structure associated  
4           with said second requester.

1           38. The system of claim 27, further comprising means  
2           for selecting a thread pool to service said request from a  
3           request set of one or more eligible thread pools, wherein  
4           the selecting is based on an ordering of said one or more  
5           eligible thread pools.

1           39. The system of claim 38, wherein the ordering  
2 comprises having a primary thread pool selectable before any  
3 secondary thread pool.

1           40. The system of claim 27, wherein said means for  
2 receiving comprises means for receiving said request by a  
3 server of said computing environment, and wherein said first  
4 requester is a first client and said second requester is a  
5 second client.

1           41. The system of claim 40, wherein said server is a  
2 file server.

1           42. The system of claim 40, wherein at least one of  
2 said first client and said second client runs on a same  
3 physical computer of said computing environment as said  
4 server.

1           43. The system of claim 40, wherein at least one of  
2 said first client and said second client runs on a different  
3 physical computer of said computing environment than said  
4 server.

1           44. The system of claim 27, wherein the dynamically  
2 altering is performed by a server of said computing  
3 environment.



1           45. The system of claim 27, wherein said thread pool  
2 of said altered thread pool set is to service said response  
3 to avoid a deadlock with said request awaiting said  
4 response.

1           46. The system of claim 27, wherein said means for  
2 dynamically altering receives no indication from said second  
3 requester of which thread pools are to be included in said  
4 altered thread pool set.

1           47. The system of claim 27, wherein said first  
2 requester and said second requester are the same requester.

1           48. The system of claim 27, wherein said first  
2 requester and said second requester are different  
3 requesters.

1           49. A system of managing thread pools of a computing  
2 environment, said system comprising:

3                 means for dynamically determining which thread  
4 pool of a plurality of thread pools is to be used to  
5 process a request; and

6                 means for processing said request using a thread  
7 of said thread pool.

1           50. The system of claim 49, wherein the dynamically  
2 determining is performed when said request is a callback  
3 response to another request.

1           51. The system of claim 49, wherein said computing  
2 environment comprises at least one server and at least one  
3 client, and wherein said request is issued by a client of  
4 said at least one client and received by a server of said at  
5 least one server, and wherein the dynamically determining is  
6 performed by said server.

1           52. The system of claim 51, wherein said means for  
2 dynamically determining receives no indication from said  
3 client of which thread pool is to be used.

1           53. A system of managing thread pools of a computing  
2 environment, said system comprising:

3           a processor adapted to receive from a first client  
4 of said computing environment a request to be  
5 processed, said request waiting on a response from a  
6 second client of said computing environment, and  
7 wherein said response is to be serviced by a thread  
8 pool selected from a set of one or more eligible thread  
9 pools; and

10           said processor being adapted to dynamically alter  
11 said set of one or more eligible thread pools to  
12 provide an altered thread pool set of one or more  
13 eligible thread pools, wherein a thread pool of the  
14 altered thread pool set is to service said response.

1           54. The system of claim 53, wherein said processor  
2 comprises a server of said computing environment.

1           55. The system of claim 53, wherein said first client  
2 and said second client are the same client.

1           56. The system of claim 53, wherein said first client  
2 and said second client are different clients.

1           57. A system of managing thread pools of a computing  
2 environment, said system comprising:

3           a processor adapted to dynamically determine which  
4 thread pool of a plurality of thread pools is to be  
5 used to process a request; and

6           said processor being adapted to process said  
7 request using a thread of said thread pool.

1           58. At least one program storage device readable by a  
2 machine, tangibly embodying at least one program of  
3 instructions executable by the machine to perform a method  
4 of managing thread pools of a computing environment, said  
5 method comprising:

6           receiving from a first requester of said computing  
7 environment a request to be processed, said request  
8 waiting on a response from a second requester of said  
9 computing environment, and wherein said response is to  
10 be serviced by a thread pool selected from a set of one  
11 or more eligible thread pools; and

12           dynamically altering said set of one or more  
13 eligible thread pools to provide an altered thread pool  
14 set of one or more eligible thread pools, wherein a  
15 thread pool of the altered thread pool set is to  
16 service said response.

1           59. The at least one program storage device of claim  
2 58, wherein said dynamically altering comprises setting a  
3 pool mask associated with said response to indicate said one  
4 or more eligible thread pools.

1           60. The at least one program storage device of claim  
2 59, wherein said pool mask is included within a data  
3 structure associated with said response.

1           61. The at least one program storage device of claim  
2 58, wherein said dynamically altering is initiated when it  
3 is determined that said request is waiting for said  
4 response.

1           62. The at least one program storage device of claim  
2 58, wherein said method further comprises selecting said  
3 thread pool from said altered thread pool set to service  
4 said response.

1           63. The at least one program storage device of claim  
2 62, wherein said selecting comprises:

3                 determining which, if any, thread pools of said  
4 altered thread pool set were not included in said set  
5 of one or more eligible thread pools, thereby providing  
6 one or more new thread pools; and

7                 selecting said thread pool from said one or more  
8 new thread pools.

1           64. The at least one program storage device of claim  
2 58, wherein said method further comprises dispatching said  
3 response on a thread of said thread pool.

1           65. The at least one program storage device of claim  
2   64, wherein said method further comprises:

3           determining whether said thread pool is  
4   appropriate for the dispatched response; and

5           redispatching said response onto another thread  
6   pool when the thread pool is inappropriate.

1           66. The at least one program storage device of claim  
2   58, wherein said method further comprises dynamically re-  
3   altering said altered thread pool set to service one or more  
4   other responses or one or more other requests.

1           67. The at least one program storage device of claim  
2   66, wherein said dynamically re-altering is performed when  
3   there are no outstanding callbacks to be responded to by  
4   said second requester.

1           68. The at least one program storage device of claim  
2   67, wherein said method further comprises determining  
3   whether there are any outstanding callbacks, said  
4   determining referencing a data structure associated with  
5   said second requester.

1           69. The at least one program storage device of claim  
2 58, wherein said method further comprises selecting a thread  
3 pool to service said request from a request set of one or  
4 more eligible thread pools, wherein said selecting is based  
5 on an ordering of said one or more eligible thread pools.

1           70. The at least one program storage device of claim  
2 69, wherein said ordering comprises having a primary thread  
3 pool selectable before any secondary thread pool.

1           71. The at least one program storage device of claim  
2 58, wherein said receiving comprises receiving said request  
3 by a server of said computing environment, and wherein said  
4 first requester is a first client and said second requester  
5 is a second client.

1           72. The at least one program storage device of claim  
2 71, wherein said server is a file server.

1           73. The at least one program storage device of claim  
2 71, wherein at least one of said first client and said  
3 second client runs on a same physical computer of said  
4 computing environment as said server.

1           74. The at least one program storage device of claim  
2 71, wherein at least one of said first client and said  
3 second client runs on a different physical computer of said  
4 computing environment than said server.



1           75. The at least one program storage device of claim  
2 58, wherein said dynamically altering is performed by a  
3 server of said computing environment.

1           76. The at least one program storage device of claim  
2 58, wherein said thread pool of said altered thread pool set  
3 is to service said response to avoid a deadlock with said  
4 request awaiting said response.

1           77. The at least one program storage device of claim  
2 58, wherein said dynamically altering comprises receiving no  
3 indication from said second requester of which thread pools  
4 are to be included in said altered thread pool set.

1           78. The at least one program storage device of claim  
2 58, wherein said first requester and said second requester  
3 are the same requester.

1           79. The at least one program storage device of claim  
2 58, wherein said first requester and said second requester  
3 are different requesters.

1           80. An article of manufacture, comprising:

2                   at least one computer usable medium having  
3           computer readable program code means embodied therein  
4           for causing the managing of thread pools of a computing  
5           environment, the computer readable program code means  
6           in said article of manufacture comprising:

7                   computer readable program code means for  
8           causing a computer to dynamically determine which  
9           thread pool of a plurality of thread pools is to  
10          be used to process a request; and

11                  computer readable program code means for  
12          causing a computer to process said request using a  
13          thread of said thread pool.

1           81. The article of manufacture of claim 80, wherein  
2           the dynamically determining is performed when said request  
3           is a callback response to another request.

1           82. The article of manufacture of claim 80, wherein  
2           said computing environment comprises at least one server and  
3           at least one client, and wherein said request is issued by a  
4           client of said at least one client and received by a server  
5           of said at least one server, and wherein the dynamically  
6           determining is performed by said server.


1           83. The article of manufacture of claim 82, wherein  
2   the dynamically determining comprises receiving no  
3   indication from said client of which thread pool is to be  
4   used.

\* \* \* \* \*


METHOD, SYSTEM AND PROGRAM PRODUCTS FOR MANAGING  
THREAD POOLS OF A COMPUTING ENVIRONMENT  
TO AVOID DEADLOCK SITUATIONS

Abstract of the Disclosure


5           Deadlock situations within a computing environment are  
avoided by properly managing pools of threads used to  
service requests of the computing environment. When a  
server of the computing environment receives a request to be  
processed and that request is waiting on a response from a  
10 client of the computing environment, the set of eligible  
thread pools for the response is dynamically altered. This  
dynamic altering allows the response to be serviced by a  
thread pool different from the thread pool servicing the  
request, thereby avoiding a deadlock situation.




*fig. 1*



*fig. 2*




*fig. 3A*




*fig. 3B*

CREATE CLIENT SESSION



*fig. 4A*

RECEIPT OF REQUEST



*fig. 4B*

REQUEST PROCESSING






fig. 4C






SESSION




*fig. 5*

REQUEST  
BLOCK



REQUEST  
BLOCK




...


602

← REQUEST QUEUE →

*fig. 6*



*fig. 7*



## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

# METHOD, SYSTEM AND PROGRAM PRODUCTS FOR MANAGING THREAD POOLS OF A COMPUTING ENVIRONMENT TO AVOID DEADLOCK SITUATIONS

the specification of which (check one)

X is attached hereto.

\_\_\_\_\_ was filed on \_\_\_\_\_ as United States  
Application Number or PCT International Application  
Number \_\_\_\_\_ and was amended on \_\_\_\_\_.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Claimed

\_\_\_\_ Yes \_\_\_\_ No

(Number) (Country) (Day/Month/Year Filed)

\_\_\_\_ Yes      \_\_\_\_ No

(Number)      (Country)      (Day/Month/Year Filed)

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.

(Application Number)	(Filing Date)
----------------------	---------------

(Application Number) (Filing Date)

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose material information as defined in 37 CFR §1.56(a) which occurred between the filing date of the prior application and the national or PCT International filing date of this application:

(Appl. Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------	---------------	---

(Appl. Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------	---------------	---

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Christopher A. Hughes, Esq.	Reg. No. 26,914
Edward A. Pennington, Esq.	Reg. No. 32,588
John E. Hoel, Esq.	Reg. No. 26,279
Joseph C. Redmond, Jr., Esq.	Reg. No. 18,753
David L. Adour, Esq.	Reg. No. 29,604
Lawrence R. Fraley, Esq.	Reg. No. 26,885
Arthur J. Samodovitz, Esq.	Reg. No. 31,297
William H. Steinberg, Esq.	Reg. No. 28,540
John R. Pivnichny, Ph.D.	Reg. No. 43,001
Jeff Rothenberg, Esq.	Reg. No. 26,429
Kevin P. Radigan, Esq.	Reg. No. 31,789
Blanche E. Schiller, Esq.	Reg. No. 35,670

**Send Correspondence to:**

Blanche E. Schiller, Esq.  
 HESLIN & ROTHENBERG, P.C.  
 5 Columbia Circle  
 Albany, New York 12203-5160  
 Telephone: (518) 452-5600  
 Facsimile: (518) 452-5579

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

ADDED PAGE(S) TO COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR SIGNATURE BY FIRST AND SUBSEQUENT INVENTORS

Full Name of first joint inventor: **Gregory David Doolittle**

Signature: Gregory David Doolittle Date: 11/17/99

Residence: 153 Meeker Road, Vestal, NY 13850-3265

Citizenship: United States of America

Post Office Address: 153 Meeker Road, Vestal, NY 13850-3265

Full Name of second joint inventor: **Timothy Peter Krein**

Signature: Timothy Peter Krein Date: 11/16/99

Residence: 4616 Foster Valley Road, Endicott, NY 13760

Citizenship: United States of America

Post Office Address: 4616 Foster Valley Road, Endicott, NY 13760

Full Name of third joint inventor: **Scott Thomas Marcotte**

Signature: Scott Thomas Marcotte Date: 11/17/99

Residence: 337 Third Avenue, Vestal, NY 13850

Citizenship: United States of America

Post Office Address: 337 Third Avenue, Vestal, NY 13850

66677-2024460